

# SP1-V/ XBA Combo

## Smart Printer for Vending

- Design dedicated for Vending Applications
- Easy Installation and Low Maintenance
- Anti-Pull Paper Mechanism
- Adjustable Paper Length
- Low-paper Alarm Indicator
- Quick, Easy Settings & Upgrade via USB Pen-drive



# SP1-V/ XBA Combo
















## Smart Printer for Vending

SP1-V, a compact-size design, is installed on the vending machine that needs the functionality of output a receipt while the transaction completed. The friendly user interface of built-in print-button and the adjustable paper length function, the user can easy and quick operate SP1-V to increase the efficiency of paper-use and reduce the maintenance cost.

With a DAB (ICT's Data Audit Box) installation, it can satisfy the operator not only the requirements of audit transaction (DAB) but also to print out the receipt/ coupon for the vending machines.

Both coupon and receipt, the format including the logo, text contents and QR/ bar code, etc, can be set-up by the user. The downloadable design that the operator can save or upload the printing format/settings between SP1-V and utility tool via a USB pen-drive would considerable educe the maintenance efforts.

### Specifications

 <b>Printing Method</b> Thermal dot-line printing	 <b>Power Source</b> 20VDC~45VDC 24VAC
 <b>Printing Speed</b> 90±5mm/sec	 <b>Power Consumption</b> Standby: 2.4W Operation: 14.4W Maximum: 84W (in case of printing in all gray)
 <b>Paper Size</b> Width: 58±0.5 mm/ 2.28±0.02 inches Outside Diameter: 40±1.0 mm/ 1.57±0.02 inches	 <b>Dimension</b> <b>SP1-V</b> (H)132 x (W)102 x (D)155.3 mm / (H) 5.2 x (W) 4.0 x (D) 6.1 inches <b>Combo</b> (H)302.1 x (W)101.9 x (D)189.5 mm/ (H) 11.9 x (W) 4.01 x (D) 7.46 inches
 <b>Paper-Length Adjustment</b> 70~114 mm/ 2.75~4.48 inches	 <b>Weight</b> <b>SP1-V</b> Approx. 700g / 1.55 lbs(without paper roll) <b>Combo</b> Approx. 2200g / 4.85 lbs
 <b>Resolution</b> 8 dots/ mm	 <b>Environmental</b> Operation Temperature: 0°C/32°F~50°C/122°F Storage Temperature: -20°C/-4°F~60°C/140°F Humidity: 30%~85% (no condensation)
 <b>Character Set</b> 5 Font Sizes (8*13, 16*24, 24*36, 32*48, 48*72)	 <b>Certificate</b> CE, FCC
 <b>Interface</b> DAB (ICT Protocol) Setting/ Download: RS232, USB	 <b>Recommended Applications</b> Vending
 <b>Printer Mode</b> Auto Mode Button Mode	

All trademarks and copyrights mentioned herein belong to their respective owners. Specifications are subject to change without prior notice.



### International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw