

L77F/PL77-RUB4

L77F/PL77 DIP SWITCHES SETTING : 1(Pulse/ICT104/MDB)

Supported bill RUB 50, 100, 500, 1000 4bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / RUB 50	OFF	OFF	OFF							
	2 Pulse / RUB 50	OFF	OFF	ON							
	3 Pulse / RUB 50	OFF	ON	OFF							
	4 Pulse / RUB 50	OFF	ON	ON							
	5 Pulse / RUB 50	ON	OFF	OFF							
	10 Pulse / RUB 50	ON	OFF	ON							
	20 Pulse / RUB 50	ON	ON	OFF							
	100 Pulse / RUB 50	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept RUB 50				ON						
	Reject RUB 50				OFF						
★	Accept RUB 100				ON						
	Reject RUB 100				OFF						
★	Accept RUB 500				ON						
	Reject RUB 500				OFF						
★	Accept RUB 1000				ON						
	Reject RUB 1000				OFF						
★	Reserved										ON
	Reserved										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L77F/PL77-RUB4 (Pulse/ICT104/MDB)

DIP SWITCHES SETTING : 2(Pulse) Currency Assign Data

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT104 Interface		OFF	ON	
	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Bill value	ICT	Pulse	MDB
BV1	RUB 50	RUB 50	RUB 50
BV2	RUB 100	RUB 100	RUB 100
BV3	RUB 500	RUB 500	RUB 500
BV4	RUB 1000	RUB 1000	RUB 1000

DIP SWITCHES SETTING : 2(ICT)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT104 Interface		OFF	ON	
	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON	OFF	
	ICT104 Interface		OFF	ON	
★	MDB Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting