

# L83-BYN5

## L83 DIP SWITCHES SETTING : 1(Pulse/MDB)

Supported bill Br 5, 10, 20, 50, 100 5bills.

| FUNCTION   | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| ★ 1 Pulse / Br 5   | OFF | OFF | OFF |     |     |     |     |     |     |      |
| 2 Pulse / Br 5   | OFF | OFF | ON  |     |     |     |     |     |     |      |
| 3 Pulse / Br 5   | OFF | ON  | OFF |     |     |     |     |     |     |      |
| 4 Pulse / Br 5   | OFF | ON  | ON  |     |     |     |     |     |     |      |
| 5 Pulse / Br 5   | ON  | OFF | OFF |     |     |     |     |     |     |      |
| 10 Pulse / Br 5  | ON  | OFF | ON  |     |     |     |     |     |     |      |
| 20 Pulse / Br 5  | ON  | ON  | OFF |     |     |     |     |     |     |      |
| 100 Pulse / Br 5   | ON  | ON  | ON  |     |     |     |     |     |     |      |
| Fast output Pulse <small>Lo= 50ms<br/>Hi=100ms</small>   |     |     |     | ON  |     |     |     |     |     |      |
| ★ Slow output Pulse <small>Lo= 50ms<br/>Hi=300ms</small> |     |     |     | OFF |     |     |     |     |     |      |
| Inhibit level Active Low                                 |     |     |     |     | ON  |     |     |     |     |      |
| ★ Inhibit level Active High                              |     |     |     |     | OFF |     |     |     |     |      |
| ★ Accept Br 5  |     |     |     |     |     | ON  |     |     |     |      |
| Reject Br 5  |     |     |     |     |     | OFF |     |     |     |      |
| ★ Accept Br 10   |     |     |     |     |     |     | ON  |     |     |      |
| Reject Br 10   |     |     |     |     |     |     | OFF |     |     |      |
| ★ Accept Br 20   |     |     |     |     |     |     |     | ON  |     |      |
| Reject Br 20   |     |     |     |     |     |     |     | OFF |     |      |
| ★ Accept Br 50   |     |     |     |     |     |     |     |     | ON  |      |
| Reject Br 50   |     |     |     |     |     |     |     |     | OFF |      |
| ★ Accept Br 100  |     |     |     |     |     |     |     |     |     | ON   |
| Reject Br 100  |     |     |     |     |     |     |     |     |     | OFF  |

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.  
(2)Dip switches 1 to 5 are only used for pulse protocol.

# L83-BYN5(Pulse/MDB)

## DIP SWITCHES SETTING : 2(Pulse)

| FUNCTION            | SW1 | SW2 | SW3 | SW4 |
|---------------------|-----|-----|-----|-----|
| ★ Pulse Normal High | ON  |     |     |     |
| Pulse Normal Low    | OFF |     |     |     |
| ★ Pulse Mode        |     | ON  |     |     |
| MDB Mode            |     | OFF |     |     |
| ★ Reserved          |     |     | ON  |     |
|                     |     |     | OFF |     |
|                     |     |     |     | ON  |
|                     |     |     |     | OFF |

★ Manufacture setting

## DIP SWITCHES SETTING : 2(MDB)

| FUNCTION  | SW1 | SW2 | SW3 | SW4 |
|---|-----|-----|-----|-----|
| ★ Scaling Factor (SF) = 100<br>Decimal Point Position (DPP) = 2 | ON  |     |     |     |
| Scaling Factor (SF) = 1<br>Decimal Point Position (DPP) = 0     | OFF |     |     |     |
| Pulse Mode  |     | ON  |     |     |
| ★ MDB Mode  |     | OFF |     |     |
| ★ Reserved  |     |     | ON  |     |
|   |     |     | OFF |     |
|   |     |     |     | ON  |
|   |     |     |     | OFF |

★ Manufacture setting

## Currency Assign Data

| Interface<br>Bill value | Pulse  | MDB    |
|-------------------------|--------|--------|
| BV1                     | Br 5   | Br 5   |
| BV2                     | Br 10  | Br 10  |
| BV3                     | Br 20  | Br 20  |
| BV4                     | Br 50  | Br 50  |
| BV5                     | Br 100 | Br 100 |