

L83-RON8

L83 Option Switch Settings : 1(Pulse/ICT104U/MDB/RS232 A0)

Supported bill RON 1, 5, 10, 20, 50, 100, 200, 500 8bills.

L83 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / RON 1	OFF	OFF	OFF							
	2 Pulses / RON 1	OFF	OFF	ON							
	3 Pulses / RON 1	OFF	ON	OFF							
	4 Pulses / RON 1	OFF	ON	ON							
	5 Pulses / RON 1	ON	OFF	OFF							
	10 Pulses / RON 1	ON	OFF	ON							
	20 Pulses / RON 1	ON	ON	OFF							
	100 Pulses / RON 1	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept RON 1				ON						
	Reject RON 1 (Note.3)				OFF						
★	Accept RON 5				ON						
	Reject RON 5				OFF						
★	Accept RON 10 & 20				ON						
	Reject RON 10 & 20				OFF						
★	Accept RON 50 & 100				ON						
	Reject RON 50 & 100				OFF						
★	Accept RON 200 & 500				ON						
	Reject RON 200 & 500				OFF						

◆ Manufacture Default setting.

Note : (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

(3)MDB Mode:When Dip Switch 6 is turn OFF, Accept RON 500 and Reject RON 1

L83-RON8(Pulse/ICT104U/MDB/RS232 A0)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Interface		ON	OFF	
	MDB Interface		ON	ON	
	RS232 A0 Interface		OFF	OFF	
	ICT104U Interface		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 2(ICT104U)

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Interface		ON	OFF	
	MDB Interface		ON	ON	
	RS232 A0 Interface		OFF	OFF	
★	ICT104U Interface		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Interface Settings: 2(RS232 A0)

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Interface		ON	OFF	
	MDB Interface		ON	ON	
★	RS232 A0 Interface		OFF	OFF	
	ICT104U Interface		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	RON 1
2	Reserved
3	RON 5
4	RON 10
5	RON 20
6	RON 50
7	RON 100
8	RON 200
9	RON 500

Interface Settings: 2(MDB) Currency Assign Data

	Interface	MDB		Pulse	RS232 A0	ICT104U
		SW6:ON	SW6:OFF			
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON				
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF				
	Pulse Interface		ON	OFF		
★	MDB Interface		ON	ON		
	RS232 A0 Interface		OFF	OFF		
	ICT104U Interface		OFF	ON		
★	Reserved				ON	
					OFF	

★ Manufacture setting