

# NE77-EUR4

## NE77 DIP SWITCHES SETTING : (ICT104U/Pulse/ccTalk)

Supported bill EUR 5, 10, 20, 50

4bills.

### DIP SWITCHES SETTING : (ICT104U)

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
Reserved	ON									
★ Reserved	OFF									
ccTalk Potocol		ON								
★ ICT104U Potocol		OFF								
Reserved			ON							
★ Reserved			OFF							
★ Enable Output Sensor Detect				ON						
Disable Output Sensor Detect				OFF						
Reserved					ON					
★ Reserved					OFF					
Optical anti-fishing malfunction, BA will be still in working order						ON				
★ BA will stop to work when it acknowledges Optical anti-fishing malfunction						OFF				
★ Accept Euro 5							ON			
Reject Euro 5							OFF			
★ Accept Euro 10 & 20 & 50								ON		
Reject Euro 10 & 20 & 50								OFF		
★ Operation Mode									ON	
Diagnostic Mode									OFF	
Pulse Protocol										ON
★ Other Protocol										OFF

★ Manufacture setting

Note1 : Please restart the bill acceptor after any changes on dip switch(s) has been made.

Note2 : Turn this dip to with restart the bill acceptor will restore

Rs232 B1 address to its default value of 40 and the encryption key to its default value of 123456.

# NE77-EUR4 (ICT104U/Pulse/ccTalk)

## DIP SWITCHES SETTING : (Pulse)

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
5 Pulse / € 5	ON									
★ 1 Pulse / € 5	OFF									
★ Lo=150ms / Hi=180ms		OFF	OFF							
Lo=100ms / Hi=100ms		OFF	ON							
Lo= 50ms / Hi=100ms		ON	OFF							
Lo= 50ms / Hi= 50ms		ON	ON							
★ Enable Output Sensor Detect				ON						
Disable Output Sensor Detect				OFF						
Inhibit level Active High					ON					
★ Inhibit level Active Low					OFF					
Optical anti-fishing malfunction, BA will be still in working order BA will stop to work when it acknowledges Optical anti-fishing malfunction						ON				
★ Accept € 5							ON			
★ Reject € 5							OFF			
★ Accept € 10 & 20 & 50								ON		
Reject € 10 & 20 & 50								OFF		
★ Operation Mode									ON	
Diagnostic Mode									OFF	
★ Pulse Protocol										ON
Other Protocol										OFF

### DIP SWITCHES SETTING : (ccTalk)

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
Reserved	ON									
★ Reserved	OFF									
★ ccTalk Protocol		ON								
ICT104U Protocol		OFF								
★ Encyption MODE			ON							
Decrypt MODE			OFF							
★ Enable Output Sensor Detect				ON						
Disable Output Sensor Detect				OFF						
ccTalk parameters restore (Please see Note.2 for detail)					ON					
★ ccTalk parameters not restore					OFF					
Optical anti-fishing malfunction, BA will be still in working order BA will stop to work when it acknowledges Optical anti-fishing malfunction						ON				
★ Accept € 5							ON			
★ Reject € 5							OFF			
★ Accept € 10 & 20 & 50								ON		
Reject € 10 & 20 & 50								OFF		
★ Operation Mode									ON	
Diagnostic Mode									OFF	
Pulse Procotol										ON
★ Other Procotol										OFF