

## A6-USD4

### A6 Option Switch Settings:1(5V Enable/Single Price/Out of Service/ICT)

Supported bill US\$ 1, 5, 10, 20 4bills.

A6 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject US\$ 1	ON											
★	Accept US\$ 1	OFF											
★	Reject US\$ 5		ON										
★	Accept US\$ 5		OFF										
★	Reject US\$ 10			ON									
★	Accept US\$ 10			OFF									
★	Reject US\$ 20				ON								
★	Accept US\$ 20				OFF								
★	Reserved				ON								
★	Reserved				OFF								
★	High Acceptance					ON							
★	High Security					OFF							
★	Harness Disable						ON						
★	Harness Enable						OFF						
★	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulse / US\$ 1								OFF	OFF			
	2 pulse / US\$ 1								ON	OFF			
	4 pulse / US\$ 1								OFF	ON			
	20 pulse / US\$ 1								ON	ON			
★	Pulse Speed	50ms on / 50ms off									OFF	OFF	
		60ms on / 300ms off									ON	OFF	
		30ms on / 50ms off									OFF	ON	
		150ms on / 150ms off									ON	ON	

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

## A6-USD4

### A6 Interface Settings: 3(5V Enable/Single Price/Out of Service/ICT)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
★	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
★	ICT Interface		OFF		
★	Out of service normal LOW			ON	
	Out of service normal High			OFF	
	Panel LED ON				ON
★	Panel LED Flashing				OFF

★ Manufacture setting

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
★	Pulse Mode		ON		
★	ICT Interface		OFF		
★	Reserved			ON	
				OFF	
	Panel LED ON				ON
★	Panel LED Flashing				OFF

★ Manufacture setting

### Currency Assign Data

Interface Bill value	Pulse	ICT
BV1	US\$ 1	US\$ 1
BV2	US\$ 5	US\$ 5
BV3	US\$ 10	US\$ 10
BV4	US\$ 20	US\$ 20