

A7/V7-BHD3

A7/V7 Option Switch Settings

Supported bill BD 1/2(97), 1(93), 5(98) 3bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject BD ½	ON											
Accept BD ½	OFF											
Reject BD 1		ON										
Accept BD 1		OFF										
Reject BD 5			ON									
Accept BD 5			OFF									
Reserved				ON								
Reserved				OFF								
Reserved					ON							
Reserved					OFF							
High Acceptance						ON						
High Security						OFF						
Harness disable							ON					
Harness enable							OFF					
Inhibit Active High								ON				
Inhibit Active Low								OFF				
★ 1 pulse / BD ½									OFF	OFF		
★ 2 pulse / BD ½									ON	OFF		
4 pulse / BD ½									OFF	ON		
20 pulse / BD ½									ON	ON		
★ Pulse Speed	50ms on / 50ms off								OFF	OFF		
	60ms on / 300ms off								ON	OFF		
	30ms on / 50ms off								OFF	ON		
	150ms on / 150ms off								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A7/V7-BHD3

A7 Interface Settings: 2

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ RS232 Interface		OFF		
HOLD			ON	
			OFF	
				ON
				OFF

V7 Interface Settings: 3

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
HOLD			ON	
			OFF	
				ON
				OFF