

A7/V7-DKK2

A7/V7 Option Switch Settings

Supported bill DKK 50(99, 05), 100(99, 02) 2bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject DKK 50	ON											
Accept DKK 50	OFF											
Reject DKK 100		ON										
Accept DKK 100		OFF										
Reserved			ON									
Reserved			OFF									
Reserved				ON								
Reserved				OFF								
Reserved					ON							
Reserved					OFF							
High Acceptance						ON						
High Security						OFF						
Harness disable							ON					
Harness enable							OFF					
Inhibit Active High								ON				
Inhibit Active Low								OFF				
1 pulse / DKK 10									OFF	OFF		
5 pulse / DKK 10									ON	OFF		
10 pulse / DKK 10									OFF	ON		
20 pulse / DKK 10									ON	ON		
Pulse Speed	50ms on / 50ms off										OFF	OFF
	60ms on / 300ms off										ON	OFF
	30ms on / 50ms off										OFF	ON
	150ms on / 150ms off										ON	ON

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A7/V7-DKK2

A7 Interface Settings: 2

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ RS232 Interface		OFF		
HOLD			ON	
			OFF	
				ON
				OFF

V7 Interface Settings: 3

INTERFACE	SW1	SW2	SW3	SW4
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	ON			
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
Credit divided by 10 (Note 1)			ON	
★ Normal			OFF	
HOLD				ON
				OFF

★ Manufacture setting

◆ Note: Refer to "SW1" setting.

