

A7/V7 Option Switch Settings

Supported bill KZT 100(93), 200(99), 500(99), 1000(00), 2000(00) 5bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4	
Reject KZT 100	ON												
Accept KZT 100	OFF												
Reject KZT 200		ON											
Accept KZT 200		OFF											
Reject KZT 500			ON										
Accept KZT 500			OFF										
Reject KZT 1000				ON									
Accept KZT 1000				OFF									
Reject KZT 2000					ON								
Accept KZT 2000					OFF								
HOLD													ON
													OFF
Harness disable							ON						
Harness enable							OFF						
Inhibit Active High								ON					
Inhibit Active Low								OFF					
1 pulse / 100 Tenge									OFF	OFF			
2 pulse / 100 Tenge									ON	OFF			
4 pulse / 100 Tenge									OFF	ON			
20 pulse / 100 Tenge									ON	ON			
Pulse Speed	50ms on / 50ms off										OFF	OFF	
	60ms on / 300ms off										ON	OFF	
	30ms on / 50ms off										OFF	ON	
	150ms on / 150ms off										ON	ON	

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.