

A7/V7-SEK4

A7/V7 Option Switch Settings

Supported bill Skr 20, 50, 100, 200 4bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject Skr 20	ON											
★ Accept Skr 20	OFF											
★ Reject Skr 50		ON										
★ Accept Skr 50		OFF										
★ Reject Skr 100			ON									
★ Accept Skr 100			OFF									
★ Reject Skr 200				ON								
★ Accept Skr 200				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
★ Harness disable							ON					
★ Harness enable							OFF					
★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / Skr 10									OFF	OFF		
2 pulse / Skr 10									ON	OFF		
4 pulse / Skr 10									OFF	ON		
20 pulse / Skr 10									ON	ON		
★ Pulse Speed	50ms LO / 50ms HI								OFF	OFF		
	60ms LO / 300ms HI								ON	OFF		
	30ms LO / 50ms HI								OFF	ON		
	150ms LO / 150ms HI								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A7/V7-SEK4(Pulse/MDB)

A7 Interface Settings: 3

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

V7 Interface Settings: 3

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	Skr 20	Skr 20
BV2	Skr 50	Skr 50
BV3	Skr 100	Skr 100
BV4	Skr 200	Skr 200