

# A7/V7-KRW3

## A7/V7 Option Switch Settings : 1

Supported bill ₩ 1000, 5000, 10000 3 bills.

V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject ₩ 1000	ON											
★ Accept ₩ 1000	OFF											
★ Reject ₩ 5000		ON										
★ Accept ₩ 5000		OFF										
★ Reject ₩ 10000			ON									
★ Accept ₩ 10000			OFF									
★ Reserved				ON								
★ Reserved				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
★ Harness Disable							ON					
★ Harness Enable							OFF					
★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / ₩ 1000									OFF	OFF		
★ 2 pulse / ₩ 1000									ON	OFF		
★ 10 pulse / ₩ 1000									OFF	ON		
★ 20 pulse / ₩ 1000									ON	ON		
★ Pulse Speed	50ms on / 50ms off								OFF	OFF		
	60ms on / 300ms off								ON	OFF		
	30ms on / 50ms off								OFF	ON		
	150ms on / 150ms off								ON	ON		

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

# A7/V7-KRW3

## A7/V7 Interface Settings: 2 (Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
★ RS232 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

## A7/V7 Interface Settings: 3 (RS232)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
★ Pulse Mode		ON		
★ RS232 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

## V7 Interface Settings: 2 (Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
★ MDB Interface (Note 1)		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

Note: (1) Please refer to the dip-switch #1 of internal dip-switch for MDB Decimal Point Setup.

## V7 Interface Settings: 3 (MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 10 Decimal Point Position (DPP) = 1	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
★ Pulse Mode		ON		
★ MDB Interface (Note 1)		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

(2)

Interface Bill value	ICT	Pulse	MDB
BV1	₩ 1000	₩ 1000	₩ 1000
BV2	₩ 5000	₩ 5000	₩ 5000
BV3	₩ 10000	₩ 10000	₩ 10000