

## L70+/L70F-AZN5

### L70+/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U/ICT104V/MDB)

Supported bill MANAT 1, 5, 10, 20, 50 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / MANAT 1	OFF	OFF	OFF							
2 Pulse / MANAT 1	OFF	OFF	ON							
3 Pulse / MANAT 1	OFF	ON	OFF							
4 Pulse / MANAT 1	OFF	ON	ON							
5 Pulse / MANAT 1	ON	OFF	OFF							
10 Pulse / MANAT 1	ON	OFF	ON							
20 Pulse / MANAT 1	ON	ON	OFF							
100 Pulse / MANAT 1	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept MANAT 1						ON				
Reject MANAT 1						OFF				
★ Accept MANAT 5							ON			
Reject MANAT 5							OFF			
★ Accept MANAT 10								ON		
Reject MANAT 10								OFF		
★ Accept MANAT 20									ON	
Reject MANAT 20									OFF	
★ Accept MANAT 50										ON
Reject MANAT 50										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

## L70+/L70F-AZN5(Pulse/ICT104U/ICT104V/MDB)

### DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
Reserved				ON
				OFF

★ Manufacture setting

### DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
Reserved				ON
				OFF

★ Manufacture setting

### Currency Assign Data

Interface Bill value	MDB	Pulse	ICT104U	ICT104V
BV1	MANAT 1	MANAT 1	MANAT 1	MANAT 1
BV2	MANAT 5	MANAT 5	MANAT 5	MANAT 5
BV3	MANAT 10	MANAT 10	MANAT 10	MANAT 10
BV4	MANAT 20	MANAT 20	MANAT 20	MANAT 20
BV5	MANAT 50	MANAT 50	MANAT 50	MANAT 50

### DIP SWITCHES SETTING : 2(ICT104V)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
★ ICT104V Mode		OFF	OFF	
Reserved				ON
				OFF

★ Manufacture setting

### DIP SWITCHES SETTING : 2(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Mode		OFF	ON	
MDB Mode		ON	ON	
ICT104V Mode		OFF	OFF	
Reserved				ON
				OFF

★ Manufacture setting