

L70-COP7

L70/P5 DIP SWITCHES SETTING : 1(Pulse/MDB/RS232 A0)

Supported bill COL\$ 1000, 2000, 5000, 10000, 20000, 50000, 100000 7bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / COL\$ 1000	OFF	OFF	OFF							
2 Pulses / COL\$ 1000	OFF	OFF	ON							
3 Pulses / COL\$ 1000	OFF	ON	OFF							
4 Pulses / COL\$ 1000	OFF	ON	ON							
5 Pulses / COL\$ 1000	ON	OFF	OFF							
10 Pulses / COL\$ 1000	ON	OFF	ON							
20 Pulses / COL\$ 1000	ON	ON	OFF							
100 Pulses / COL\$ 1000	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low				ON						
Inhibit level Active High				OFF						
★ Accept COL\$ 1000 & 2000				ON						
★ Reject COL\$ 1000 & 2000				OFF						
★ Accept COL\$ 5000				ON						
★ Reject COL\$ 5000				OFF						
★ Accept COL\$ 10000				ON						
★ Reject COL\$ 10000				OFF						
★ Accept COL\$ 20000				ON						
★ Reject COL\$ 20000				OFF						
★ Accept COL\$ 50000 & 100000				ON						
★ Reject COL\$ 50000 & 100000				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70-COP7/P5(Pulse/MDB/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
RS232 A0 Mode		OFF	OFF	
MDB Mode		ON	ON	
Reserved		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB	RS232 A0
BV1	COL\$ 1000	COL\$ 1000	COL\$ 1000
BV2	COL\$ 2000	COL\$ 2000	COL\$ 2000
BV3	COL\$ 5000	COL\$ 5000	COL\$ 5000
BV4	COL\$ 10000	COL\$ 10000	COL\$ 10000
BV5	COL\$ 20000	COL\$ 20000	COL\$ 20000
BV6	COL\$ 50000	COL\$ 50000	COL\$ 50000
BV7	COL\$100000	COL\$100000	COL\$100000

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON	OFF	
★ RS232 A0 Mode		OFF	OFF	
MDB Mode		ON	ON	
Reserved		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	COL\$ 1000
2	COL\$ 2000
3	COL\$ 5000
4	COL\$ 10000
5	COL\$ 20000
6	COL\$ 50000
7	COL\$ 100000
8	Reserved
9	Reserved

DIP SWITCHES SETTING : 2(MDB)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 10 Decimal Point Position (DPP) = 1	ON			
	OFF			
Pulse Mode		ON	OFF	
★ RS232 A0 Mode		OFF	OFF	
MDB Mode		ON	ON	
Reserved		OFF	ON	
★ Reserved				ON
				OFF

★ Manufacture setting