L70-GTQ4

L70/P5 DIP SWITCHES SETTING: 1(Pulse/ICT104U) Supported bill GTQ 10, 20, 50, 100 4bills.

Γ	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
⋆┞	1 Pulse / GTQ 10	OFF	OFF	OFF							
^ 	2 Pulse / GTQ 10	OFF	OFF	ON							
╂		OFF	ON	OFF							
ŀ	3 Pulse / GTQ 10										
ŀ	4 Pulse / GTQ 10	OFF	ON	ON							
ŀ	5 Pulse / GTQ 10	ON	OFF	OFF							
L	10 Pulse / GTQ 10	ON	OFF	ON							
	20 Pulse / GTQ 10	ON	ON	OFF							
1	100 Pulse / GTQ 10	ON	ON	ON							
Γ	Fast output Pulse Lo= 50ms Hi=100ms				ON						
* [Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
*[Inhibit level Active High					OFF					
* [Accept GTQ 10						ON				
1	Reject GTQ 10						OFF				
⋆[Accept GTQ 20							ON			
	Reject GTQ 20							OFF			
* [Accept GTQ 50								ON		
1	Reject GTQ 50								OFF		
* [Accept GTQ 100									ON	
	Reject GTQ 100									OFF	
⋆┃	Reserve										ON
	Reserve										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L70-GTQ4/P5(Pulse/ICT104U)

DIP SWITCHES SETTING: 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
*	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
*	Pulse Mode		ON		
	ICT104U Interface Mode		OFF		
*	Description			ON	
				OFF	
	Reserved		ON		
*			OFF		

[★] Manufacture setting

DIP SWITCHES SETTING: 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
*	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
*	ICT104U Interface Mode		OFF		
*	Reserved			ON	
*			OFF		

[★] Manufacture setting

Currency Assign Data

Interface Bill value	ICT	Pulse
BV1	GTQ 10	GTQ 10
BV2	GTQ 20	GTQ 20
BV3	GTQ 50	GTQ 50
BV4	GTQ 100	GTQ 100