

L70+/L70F-USD6

L70+/L70F/P5 DIP SWITCHES SETTING : 1(Pulse/ccTalk/ICT104U)

Supported bill US\$ 1, 5, 10, 20, 50, 100 6bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / US\$ 1	OFF	OFF	OFF							
2 Pulses / US\$ 1	OFF	OFF	ON							
3 Pulses / US\$ 1	OFF	ON	OFF							
4 Pulses / US\$ 1	OFF	ON	ON							
5 Pulses / US\$ 1	ON	OFF	OFF							
10 Pulses / US\$ 1	ON	OFF	ON							
20 Pulses / US\$ 1	ON	ON	OFF							
100 Pulses / US\$ 1	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept US\$ 1						ON				
Reject US\$ 1						OFF				
★ Accept US\$ 5							ON			
Reject US\$ 5							OFF			
★ Accept US\$ 10								ON		
Reject US\$ 10								OFF		
★ Accept US\$ 20									ON	
Reject US\$ 20									OFF	
★ Accept US\$ 50 & 100										ON
Reject US\$ 50 & 100										OFF

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

(3)Turn this dip to with restart the bill acceptor will restore RS232 B1 address to its default value of 40 and the encryption key to its default value of 123456

L70+/L70F-USD6(Pulse/ccTalk/ICT104U)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON	OFF	
ccTalk Interface		OFF	OFF	
ccTalk Parameters Restore Switch Please see "Note" for detail		OFF	ON	
ICT104U Interface		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	ICT104U	Pulse	ccTalk
BV1	US\$ 1	US\$ 1	US\$ 1
BV2	US\$ 5	US\$ 5	US\$ 5
BV3	US\$ 10	US\$ 10	US\$ 10
BV4	US\$ 20	US\$ 20	US\$ 20
BV5	US\$ 50	US\$ 50	US\$ 50
BV6	US\$ 100	US\$ 100	US\$ 100

DIP SWITCHES SETTING : 2(ccTalk)

FUNCTION	SW1	SW2	SW3	SW4
★ 8-bit checksum	ON			
CRC 16-bit checksum	OFF			
Pulse Mode		ON	OFF	
★ ccTalk Interface		OFF	OFF	
ccTalk Parameters Restore Switch Please see "Note" for detail		OFF	ON	
ICT104U Interface		ON	ON	
★ Encryption Mode				ON
Decrypt Mode				OFF

★ Manufacture setting

Note: Put this switch to on and reset power will restore the ccTalk address to its default value of 40 and the encryption key to its default value of 123456.

Decrypt MODE

	8-bit	CRC 16-bit
Encryption MODE	Reserved	ON
Decrypt MODE	Reserved	OFF

DIP SWITCHES SETTING : 2(ICT104U)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
ccTalk Interface		OFF	OFF	
ccTalk Parameters Restore Switch Please see "Note" for detail		OFF	ON	
★ ICT104U Interface		ON	ON	
★ Reserved				ON
				OFF

★ Manufacture setting