

V7E/LX7-GEL6

V7E/LX7 Option Switch Settings: 1(Pulse/ICT104U/RS232 A0/ccNet)

Supported bill GEL 5, 10, 20, 50, 100, 200 6 bills.

V7E/LX7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject GEL 5	ON											
	Accept GEL 5	OFF											
	Reject GEL 10		ON										
★	Accept GEL 10		OFF										
	Reject GEL 20			ON									
★	Accept GEL 20			OFF									
	Reject GEL 50				ON								
★	Accept GEL 50				OFF								
	Reject GEL 100					ON							
★	Accept GEL 100					OFF							
	Reject GEL 200						ON						
★	Accept GEL 200						OFF						
	Harness Disable							ON					
★	Harness Enable							OFF					
	Inhibit Active High								ON				
★	Inhibit Active Low								OFF				
★	1 pulse / GEL 5									OFF	OFF		
	2 pulses / GEL 5									ON	OFF		
	5 pulses / GEL 5									OFF	ON		
	20 pulses / GEL 5									ON	ON		
★	Pulse Speed	50ms LO / 50ms HI								OFF		OFF	
		60ms LO / 300ms HI								ON		OFF	
		30ms LO / 50ms HI								OFF		ON	
		150ms LO / 150ms HI								ON		ON	

★ Manufacture setting

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

(3) Default setting.

V7E/LX7-GEL6(Pulse/ICT104U/RS232 A0/ccNet)

DIP SWITCHES SETTING: 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

DIP SWITCHES SETTING: 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

DIP SWITCHES SETTING: 2(ccNet)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
	9600 Baud rate	OFF			
★	Pulse Mode		ON	OFF	
	ICT104U Mode		OFF	OFF	
★	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface	ICT104U	Pulse	RS232 A0	ccNet
BV1	GEL 5	GEL 5	GEL 5	GEL 5
BV2	GEL 10	GEL 10	GEL 10	GEL 10
BV3	GEL 20	GEL 20	GEL 20	GEL 20
BV4	GEL 50	GEL 50	GEL 50	GEL 50
BV5	GEL 100	GEL 100	GEL 100	GEL 100
BV6	GEL 200	GEL 200	GEL 200	GEL 200

DIP SWITCHES SETTING: 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
	ICT104U Mode		OFF	OFF	
★	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	Reserved
2	Reserved
3	GEL 5
4	GEL 10
5	GEL 20
6	GEL 50
7	GEL 100
8	GEL 200