



AED5

P70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill Dh 5, 10, 20, 50, 100 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
* 1 Pulse / Dh 5	OFF	OFF	OFF							
2 Pulse / Dh 5	OFF	OFF	ON							
3 Pulse / Dh 5	OFF	ON	OFF							
4 Pulse / Dh 5	OFF	ON	ON							
5 Pulse / Dh 5	ON	OFF	OFF							
10 Pulse / Dh 5	ON	OFF	ON							
20 Pulse / Dh 5	ON	ON	OFF							
100 Pulse / Dh 5	ON	ON	ON							
Fast output Pulse <small>Lo=50ms Hi=100ms</small>				ON						
* Slow output Pulse <small>Lo=50ms Hi=300ms</small>				OFF						
Inhibit level Active Low					ON					
* Inhibit level Active High					OFF					
* Accept Dh 5						ON				
Reject Dh 5						OFF				
* Accept Dh 10							ON			
Reject Dh 10							OFF			
* Accept Dh 20								ON		
Reject Dh 20								OFF		
* Accept Dh 50									ON	
Reject Dh 50									OFF	
* Accept Dh 100										ON
Reject Dh 100										OFF

* Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
* Pulse Normal High	ON			
Pulse Normal Low	OFF			
* Pulse Protocol			ON	
ICT Protocol			OFF	
Harness Disable			ON	
* Harness Enable			OFF	
Ignore Sensor Problem(Note 1)				ON
* Acknowledge Sensor Problem (Note 2)				OFF

* Manufacture setting

Note : (1) Sensor 6 problem occurred ==>> BA will be still in working order.

(The face LED will be flashing in short green about 2 seconds everytime you restart BA.)

(2) BA will stop to work when it acknowledges Sensor 6 problem occurred.

(The face LED will be flashing in red.)

