

GEL7

P70/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill GEL 1, 2, 5, 10, 20, 50, 100 7bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / GEL 1	OFF	OFF	OFF							
	2 Pulses / GEL 1	OFF	OFF	ON							
	3 Pulses / GEL 1	OFF	ON	OFF							
	4 Pulses / GEL 1	OFF	ON	ON							
	5 Pulses / GEL 1	ON	OFF	OFF							
	10 Pulses / GEL 1	ON	OFF	ON							
	20 Pulses / GEL 1	ON	ON	OFF							
	100 Pulses / GEL 1	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept GEL 1 & 2						ON				
	Reject GEL 1 & 2						OFF				
★	Accept GEL 5 & 10							ON			
	Reject GEL 5 & 10							OFF			
★	Accept GEL 20								ON		
	Reject GEL 20								OFF		
★	Accept GEL 50									ON	
	Reject GEL 50									OFF	
★	Accept GEL 100										ON
	Reject GEL 100										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1 to 5 are only used for pulse protocol.

P70-GEL7/P5(Pulse/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	RS232 A0 Interface		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4	RS232 A0 INFORMATION																		
	Not used	ON				<table border="1"> <thead> <tr> <th colspan="2">BillType Data</th> </tr> <tr> <th>Code</th> <th>Denomination</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GEL 1</td> </tr> <tr> <td>2</td> <td>GEL 2</td> </tr> <tr> <td>3</td> <td>GEL 5</td> </tr> <tr> <td>4</td> <td>GEL 10</td> </tr> <tr> <td>5</td> <td>GEL 20</td> </tr> <tr> <td>6</td> <td>GEL 50</td> </tr> <tr> <td>7</td> <td>GEL 100</td> </tr> </tbody> </table>	BillType Data		Code	Denomination	1	GEL 1	2	GEL 2	3	GEL 5	4	GEL 10	5	GEL 20	6	GEL 50	7	GEL 100
BillType Data																								
Code	Denomination																							
1	GEL 1																							
2	GEL 2																							
3	GEL 5																							
4	GEL 10																							
5	GEL 20																							
6	GEL 50																							
7	GEL 100																							
	Pulse Mode		ON																					
★		RS232 A0 Interface		OFF																				
	Harness Disable			ON																				
★	Harness Enable			OFF																				
	Manufacture Default				ON																			
★	System Default				OFF																			

★ Manufacture setting