

GEL7

P70/P5 DIP SWITCHES SETTING : 1(Pulse/ccNet)

Supported bill GEL 1, 2, 5, 10, 20, 50, 100 7bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / GEL 1	OFF	OFF	OFF							
	2 Pulses / GEL 1	OFF	OFF	ON							
	3 Pulses / GEL 1	OFF	ON	OFF							
	4 Pulses / GEL 1	OFF	ON	ON							
	5 Pulses / GEL 1	ON	OFF	OFF							
	10 Pulses / GEL 1	ON	OFF	ON							
	20 Pulses / GEL 1	ON	ON	OFF							
	100 Pulses / GEL 1	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept GEL 1 & 2						ON				
	Reject GEL 1 & 2						OFF				
★	Accept GEL 5 & 10							ON			
	Reject GEL 5 & 10							OFF			
	Accept GEL 20								ON		
★	Reject GEL 20								OFF		
	Accept GEL 50									ON	
★	Reject GEL 50									OFF	
	Accept GEL 100										ON
★	Reject GEL 100										OFF

(★) Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

P70-GEL7/P5(Pulse/ccNet)

DIP SWITCHES SETTING : 2

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	ccNet		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 & 3 are only used for pulse protocol.