



HNL6

P70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill L 5, 10, 20, 50, 100, 500

6bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / L 5	OFF	OFF	OFF							
2 Pulse / L 5	OFF	OFF	ON							
3 Pulse / L 5	OFF	ON	OFF							
4 Pulse / L 5	OFF	ON	ON							
5 Pulse / L 5	ON	OFF	OFF							
10 Pulse / L 5	ON	OFF	ON							
20 Pulse / L 5	ON	ON	OFF							
100 Pulse / L 5	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
Inhibit level Active Low					ON					
★ Inhibit level Active High					OFF					
★ Accept L 5 & 10						ON				
Reject L 5 & 10						OFF				
★ Accept L 20							ON			
Reject L 20							OFF			
★ Accept L 50								ON		
Reject L 50								OFF		
★ Accept L 100									ON	
Reject L 100									OFF	
★ Accept L 500										ON
Reject L 500										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Protocol		ON		
ICT Protocol		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting