KRW3

P70/P5 DIP SWITCHES SETTING: 1(Pulse/ICT)

Supported bill $\ensuremath{\mathbb{W}}$ 1000, 5000, 10000 3bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
⋆	1 Pulse / ₩ 1000	OFF	OFF	OFF							
	2 Pulse / ₩ 1000	OFF	OFF	ON							
	3 Pulse / ₩ 1000	OFF	ON	OFF							
	4 Pulse / ₩ 1000	OFF	ON	ON							
	5 Pulse / ₩ 1000	ON	OFF	OFF							
	10 Pulse / ₩ 1000	ON	OFF	ON							
	20 Pulse / ₩ 1000	ON	ON	OFF							
	100 Pulse / ₩ 1000	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
⋆厂	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
⋆厂	Inhibit level Active High					OFF					
⋆厂	Accept ₩ 1000						ON				
	Reject ₩ 1000						OFF				
⋆ 🗀	Accept ₩ 5000							ON			
	Reject ₩ 5000							OFF			
* □	Accept ₩ 10000								ON]	
	Reject ₩ 10000								OFF		
⋆ 🗀	Reserved									ON	
	Reserved									OFF	
k 🗀	Reserved									•	ON
	Reserved										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING: 2

	FUNCTION	SW1	SW2	SW3	SW4
*	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
*	Pulse Protocol		ON		
	ICT Protocol		OFF		
	Harness Disable			ON	
*	Harness Enable			OFF	
	Manufacture Default				ON
*	System Default				OFF

Currency Assign Data

Interface Bill value	ICT	Pulse			
BV1	₩ 1000	₩ 1000			
BV2	₩ 5000	₩ 5000			
BV3	₩ 10000	₩ 10000			

★ Manufacture setting

Appendix

© 2012 International Currency Technologies Corporation V. 1.0 Part Number : SWA8KR310-R