

# P70-PEN5

## P70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill Soles 10, 20, 50, 100, 200 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / Soles 10	OFF	OFF	OFF							
2 Pulse / Soles 10	OFF	OFF	ON							
3 Pulse / Soles 10	OFF	ON	OFF							
4 Pulse / Soles 10	OFF	ON	ON							
5 Pulse / Soles 10	ON	OFF	OFF							
10 Pulse / Soles 10	ON	OFF	ON							
20 Pulse / Soles 10	ON	ON	OFF							
100 Pulse / Soles 10	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low					ON					
Inhibit level Active High					OFF					
★ Accept Soles 10						ON				
Reject Soles 10						OFF				
★ Accept Soles 20							ON			
Reject Soles 20							OFF			
★ Accept Soles 50								ON		
Reject Soles 50								OFF		
★ Accept Soles 100									ON	
Reject Soles 100									OFF	
★ Accept Soles 200										ON
Reject Soles 200										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

## DIP SWITCHES SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Protocol		ON		
ICT Protocol		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 & 3 are only used for pulse protocol.

## Currency Assign Data

Interface Bill value	ICT	Pulse
BV1	10	10
BV2	20	20
BV3	50	50
BV4	100	100
BV5	200	200