

P70-PYG6

P70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT104U)

Supported bill G. 2000, 5000, 10000, 20000, 50000, 100000 6bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / G. 1000	OFF	OFF	OFF							
2 Pulse / G. 1000	OFF	OFF	ON							
3 Pulse / G. 1000	OFF	ON	OFF							
4 Pulse / G. 1000	OFF	ON	ON							
5 Pulse / G. 1000	ON	OFF	OFF							
10 Pulse / G. 1000	ON	OFF	ON							
20 Pulse / G. 1000	ON	ON	OFF							
100 Pulse / G. 1000	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low				ON						
★ Inhibit level Active High				OFF						
★ Accept G. 2000 & 5000				ON						
★ Reject G. 2000 & 5000				OFF						
★ Accept G. 10000				ON						
★ Reject G. 10000				OFF						
★ Accept G. 20000				ON						
★ Reject G. 20000				OFF						
★ Accept G. 50000				ON						
★ Reject G. 50000				OFF						
★ Accept G. 100000				ON						
★ Reject G. 100000				OFF						

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2 Currency Assign Data

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Protocol		ON		
ICT104U Protocol		OFF		
★ Harness Disable			ON	
★ Harness Enable			OFF	
★ Disable Continuous Accept				ON
★ Enable Continuous Accept				OFF

Interface Bill value	Pulse	ICT104U
BV1	G. 2000	G. 2000
BV2	G. 5000	G. 5000
BV3	G. 10000	G. 10000
BV4	G. 20000	G. 20000
BV5	G. 50000	G. 50000
BV6	G. 100000	G. 100000

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.
(2) Dip switches 1&3&4 are only used for pulse protocol.