

RON2

P70/P2/P5 DIP SWITCHES SETTING : 1(Pulse/M.D.B)

Supported bill Lei 1, 5 2bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / Lei 1	OFF	OFF	OFF							
2 Pulse / Lei 1	OFF	OFF	ON							
3 Pulse / Lei 1	OFF	ON	OFF							
4 Pulse / Lei 1	OFF	ON	ON							
5 Pulse / Lei 1	ON	OFF	OFF							
10 Pulse / Lei 1	ON	OFF	ON							
20 Pulse / Lei 1	ON	ON	OFF							
100 Pulse / Lei 1	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi= 50ms				ON						
★ Slow output Pulse Lo=100ms Hi= 100ms				OFF						
Inhibit level Active Low					ON					
Inhibit level Active High					OFF					
★ Accept Lei 1						ON				
Reject Lei 1						OFF				
★ Accept Lei 5							ON			
Reject Lei 5							OFF			
★ Reserved								ON		
Reserved								OFF		
★ Reserved									ON	
Reserved									OFF	
★ Reserved										ON
Reserved										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

P70-RON2/P2/P5(Pulse/M.D.B)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Mode		ON		
M.D.B Interface		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 3(M.D.B)

FUNCTION	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON		
★ M.D.B Interface		OFF		
★ Reserved			ON	
Reserved			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	Lei 1	Lei 1
BV2	Lei 5	Lei 5