

P70-RSD6

P70/P5 DIP SWITCHES SETTING : 1(Pulse/M.D.B/RS232 A0)

Supported bill RSD 10, 20, 50, 100, 200, 500 6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / RSD 10	OFF	OFF	OFF							
	2 Pulses / RSD 10	OFF	OFF	ON							
	3 Pulses / RSD 10	OFF	ON	OFF							
	4 Pulses / RSD 10	OFF	ON	ON							
	5 Pulses / RSD 10	ON	OFF	OFF							
	10 Pulses / RSD 10	ON	OFF	ON							
	20 Pulses / RSD 10	ON	ON	OFF							
	100 Pulses / RSD 10	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept RSD 10 & 20						ON				
	Reject RSD 10 & 20						OFF				
★	Accept RSD 50							ON			
	Reject RSD 50							OFF			
★	Accept RSD 100								ON		
	Reject RSD 100								OFF		
★	Accept RSD 200									ON	
	Reject RSD 200									OFF	
★	Accept RSD 500										ON
	Reject RSD 500										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

P70-RSD6(Pulse/M.D.B/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal High	ON			
	Credit-Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	Other Interface		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(M.D.B)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON		
★	Other Interface		OFF		
★	Reserved			ON	
				OFF	
★	RS232 A0 Protocol				ON
★	MDB Protocol (SW2 OFF)				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
★	Other Interface		OFF		
★	Reserved			ON	
				OFF	
★	RS232 A0 Protocol (SW2 OFF)				ON
	MDB Protocol				OFF

★ Manufacture setting

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	RSD 10
2	RSD 20
3	RSD 50
4	RSD 100
5	RSD 200
6	RSD 500

Currency Assign Data

Interface Bill value	Pulse	MDB	RS232 A0
BV1	RSD 10	RSD 10	RSD 10
BV2	RSD 20	RSD 20	RSD 20
BV3	RSD 50	RSD 50	RSD 50
BV4	RSD 100	RSD 100	RSD 100
BV5	RSD 200	RSD 200	RSD 200
BV6	RSD 500	RSD 500	RSD 500