



TJK6

P70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill TJK 1, 5, 10, 20, 50, 100 6 bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	
★	1 Pulse / TJK 1	OFF	OFF	OFF								
	2 Pulse / TJK 1	OFF	OFF	ON								
	3 Pulse / TJK 1	OFF	ON	OFF								
	4 Pulse / TJK 1	OFF	ON	ON								
	5 Pulse / TJK 1	ON	OFF	OFF								
	10 Pulse / TJK 1	ON	OFF	ON								
	20 Pulse / TJK 1	ON	ON	OFF								
	100 Pulse / TJK 1	ON	ON	ON								
	Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON							
★	Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF							
	Inhibit level Active Low					ON						
★	Inhibit level Active High					OFF						
★	Accept TJK 1 & 5						ON					
	Reject TJK 1 & 5						OFF					
★	Accept TJK 10							ON				
	Reject TJK 10							OFF				
★	Accept TJK 20								ON			
	Reject TJK 20								OFF			
★	Accept TJK 50									ON		
	Reject TJK 50									OFF		
★	Accept TJK 100										ON	
	Reject TJK 100										OFF	

★ **Manufacture setting**

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Protocol		ON		
	ICT Protocol		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Ignore Sensor Problem(Note 1)				ON
★	Acknowledge Sensor Problem (Note 2)				OFF

★ **Manufacture setting**

Note : (1) Sensor 6 problem occurred ==>> BA will be still in working order.

(The face LED will be flashing in short green about 2 seconds everytime you restart BA.)

(2) BA will stop to work when it acknowledges Sensor 6 problem occurred.

(The face LED will be flashing in red.)

