

P77-KGS7

P77/P5 DIP SWITCHES SETTING : 1(Pulse/ccNet/RS232 A0)

Supported bill KGS 20, 50, 100, 200, 500, 1000, 5000 7bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / KGS 10 & 50 (Note.3)	OFF	OFF	OFF							
2 Pulses / KGS 10 & 50 (Note.3)	OFF	OFF	ON							
3 Pulses / KGS 10 & 50 (Note.3)	OFF	ON	OFF							
4 Pulses / KGS 10 & 50 (Note.3)	OFF	ON	ON							
5 Pulses / KGS 10 & 50 (Note.3)	ON	OFF	OFF							
10 Pulses / KGS 10 & 50 (Note.3)	ON	OFF	ON							
20 Pulses / KGS 10 & 50 (Note.3)	ON	ON	OFF							
100 Pulses / KGS 10 & 50 (Note.3)	ON	ON	ON							
Fast output Pulse Lo= 50ms Hi=100ms				ON						
★ Slow output Pulse Lo= 50ms Hi=300ms				OFF						
Inhibit level Active Low				ON						
★ Inhibit level Active High				OFF						
★ Accept KGS 20				ON						
Reject KGS 20				OFF						
★ Accept KGS 50 & 100				ON						
Reject KGS 50 & 100				OFF						
★ Accept KGS 200 & 500				ON						
Reject KGS 200 & 500				OFF						
★ Accept KGS 1000				ON						
Reject KGS 1000				OFF						
★ Accept KGS 5000				ON						
Reject KGS 5000				OFF						

(★) Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

(3)Pulse Mode:

When Dip 6 is ON ,One Pulse per KGS 10.

When Dip 6 is OFF,One Pulse per KGS 50.

P77-KGS7(Pulse/ccNet/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

FUNCTION	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Protocol		ON		
Other Protocol		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
Reserved				ON
★ Reserved				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(ccNet)

FUNCTION	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Protocol		ON		
★ Other Protocol		OFF		
Reserved			ON	
★ Reserved			OFF	
★ ccNet Protocol (Sw2 OFF)				ON
RS232 A0 Protocol				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

FUNCTION	SW1	SW2	SW3	SW4
Reserved	ON			
★ Reserved	OFF			
Pulse Mode		ON		
★ Other Protocol		OFF		
Reserved			ON	
★ Reserved			OFF	
ccNet Protocol				ON
★ RS232 A0 Protocol(SW2 OFF)				OFF

★ Manufacture setting

RS232 A0 INFORMATION	
BillType Data	
Code	Denomination
1	KGS 20
2	KGS 50
3	KGS 100
4	KGS 200
5	KGS 500
6	KGS 1000
7	KGS 5000

Currency Assign Data

Interface Bill value	Pulse		RS232 A0	ccNet
	Dip 6 ON	Dip 6 OFF		
BV1	KGS 20		KGS 20	KGS 20
BV2	KGS 50	KGS 50	KGS 50	KGS 50
BV3	KGS 100	KGS 100	KGS 100	KGS 100
BV4	KGS 200	KGS 200	KGS 200	KGS 200
BV5	KGS 500	KGS 500	KGS 500	KGS 500
BV4	KGS 1000	KGS 1000	KGS 1000	KGS 1000
BV5	KGS 5000	KGS 5000	KGS 5000	KGS 5000