



# KRW3

## P77/P5 DIP SWITCHES SETTING : 1 (Pulse/ MDB)

Supported bill ₩ 1000, 5000, 10000 3bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / ₩ 1000	OFF	OFF	OFF							
	2 Pulse / ₩ 1000	OFF	OFF	ON							
	3 Pulse / ₩ 1000	OFF	ON	OFF							
	4 Pulse / ₩ 1000	OFF	ON	ON							
	5 Pulse / ₩ 1000	ON	OFF	OFF							
	10 Pulse / ₩ 1000	ON	OFF	ON							
	20 Pulse / ₩ 1000	ON	ON	OFF							
	100 Pulse / ₩ 1000	ON	ON	ON							
	Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★	Slow output Pulse <small>Lo= 50ms Hi=200ms</small>				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept ₩ 1000						ON				
	Reject ₩ 1000						OFF				
★	Accept ₩ 5000							ON			
	Reject ₩ 5000							OFF			
★	Accept ₩ 10000									ON	
	Reject ₩ 10000									OFF	
	Reserved									ON	
★	Reserved									OFF	
	Reserved										ON
★	Reserved										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

**DIP SWITCHES SETTING : 2(Pulse)**

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting

**DIP SWITCHES SETTING : 2(MDB)**

	FUNCTION	SW1	SW2	SW3	SW4
	Scaling Factor (SF) = 1000 Decimal Point Position (DPP) = 0	ON			
★	Scaling Factor (SF) = 10000 Decimal Point Position (DPP) = 1	OFF			
	Pulse Mode		ON		
★	MDB Interface		OFF		
	Reserved			ON	
★					OFF
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting