



**LAK7**

**P77/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)**

**Supported bill KIP 500, 1000, 2000, 5000, 10000, 20000, 50000 7bills.**

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	
★	1 Pulse / KIP 500	OFF	OFF	OFF								
	2 Pulse / KIP 500	OFF	OFF	ON								
	3 Pulse / KIP 500	OFF	ON	OFF								
	4 Pulse / KIP 500	OFF	ON	ON								
	5 Pulse / KIP 500	ON	OFF	OFF								
	10 Pulse / KIP 500	ON	OFF	ON								
	20 Pulse / KIP 500	ON	ON	OFF								
	100 Pulse / KIP 500	ON	ON	ON								
	Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON							
★	Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF							
	Inhibit level Active Low				ON							
	Inhibit level Active High				OFF							
★	Accept KIP 500					ON						
	Reject KIP 500					OFF						
★	Accept KIP 1000						ON					
	Reject KIP 1000						OFF					
★	Accept KIP 2000							ON				
	Reject KIP 2000							OFF				
★	Accept KIP 5000								ON			
	Reject KIP 5000								OFF			
★	Accept KIP 10000 & 20000 & 50000									ON		
	Reject KIP 10000 & 20000 & 50000									OFF		

★ Manufacture setting

Note: (1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

**DIP SWITCHES SETTING : 2**

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Protocol		ON		
	ICT Protocol		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
★	Manufacture Default				ON
	System Default				OFF

★ Manufacture setting

