

P85-BGN6

P85/P5 DIP SWITCHES SETTING : 1(Pulse/MDB)

Supported bill lev 2, 5, 10, 20, 50, 100 6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / lev 1	OFF	OFF	OFF							
	2 Pulse / lev 1	OFF	OFF	ON							
	3 Pulse / lev 1	OFF	ON	OFF							
	4 Pulse / lev 1	OFF	ON	ON							
	5 Pulse / lev 1	ON	OFF	OFF							
	10 Pulse / lev 1	ON	OFF	ON							
	20 Pulse / lev 1	ON	ON	OFF							
	100 Pulse / lev 1	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept lev 2 & 5				ON						
	Reject lev 2 & 5				OFF						
★	Accept lev 10				ON						
	Reject lev 10				OFF						
★	Accept lev 20				ON						
	Reject lev 20				OFF						
★	Accept lev 50				ON						
	Reject lev 50				OFF						
★	Accept lev 100				ON						
	Reject lev 100				OFF						

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

P85-BGN6(Pulse/M.D.B)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Protocol		ON		
	M.D.B Protocol		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Reserved				ON
★	Reserved				OFF

★ Manufacture setting.

DIP SWITCHES SETTING : 2(M.D.B)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Protocol		ON		
★	M.D.B Protocol		OFF		
	Reserved			ON	
★	Reserved			OFF	
	Reserved				ON
★	Reserved				OFF

★ Manufacture setting.

Currency Assign Data

Interface Bill value	MDB	Pulse
BV1	Lev 2	Lev 2
BV2	Lev 5	Lev 5
BV3	Lev 10	Lev 10
BV4	Lev 20	Lev 20
BV5	Lev 50	Lev 50
BV6	Lev 100	Lev 100