V7-BGN2

V7 Option Switch Settings: 1(Pulse/MDB) Supported bill BGN 5, 10 2bills.

V7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
	Reject BGN 5	ON											
*	Accept BGN 5	OFF											
	Reject BGN 10		ON										
*	Accept BGN 10		OFF										
	Reserved			ON									
*	Reserved			OFF									
	Reserved				ON								
*	Reserved				OFF								
	Reserved					ON							
*	Reserved					OFF							
	Reserved						ON						
*	Reserved						OFF						
	Harness disable							ON					
*	Harness enable							OFF					
	Inhibit Active High								ON				
*	Inhibit Active Low								OFF				
*	1 pulse / BGN 1	OFF OFF						OFF					
	2 pulses / BGN 1							ON	OFF				
	4 pulses / BGN 1									OFF	ON		
	20 pulses / BGN 1									ON	ON		
*		50	ms LO	/ 50n	ns HI							OFF	OFF
	Pulse Speed	60ms LO / 300ms HI 30ms LO / 50ms HI									ON	OFF	
	Fuise Speeu										OFF	ON	
		150	ms LO	/ 150m	ns HI							ON	ON

[◆] Factory configuration has all switches in the OFF position.

Note: (1) Please refer to the dip-switch #1 of internal dip-switch for MDB Decimal Point Setup.

_Appendix

V7-BGN2(Pulse/MDB)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
*	Credit-Pulse Normal HIGH	Credit-Pulse Normal HIGH ON			
	Credit-Pulse Normal LOW	OFF			
*	Pulse Mode		ON		
	MDB Interface		OFF		
	Reserved			ON	
*	Reserved			OFF	
	Reserved		ON		
*	Reserved		OFF		

[★] Manufacture setting

Interface Settings: 2(MDB)

_						
	INTERFACE		SW2	SW3	SW4	
*	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2					
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0					
*	Pulse Interface		ON			
	MDB Interface (Note)		OFF			
	Reserved			ON		
*	Reserveu			OFF		
	Reserved				ON	
*	reserved					

[★] Manufacture setting

Note: Please refer to the dip-switch #1 of internal dip-switch for MDB Decimal Point Setup.

Currency Assign Data

Interface Bill value	MDB	Pulse			
BV1	BGN 5	BGN 5			
BV2	BGN 10	BGN 10			