

V7-CLP5

V7 Option Switch Settings : 1(Pulse/ICT002)

Supported bill Ch\$ 1000, 2000, 5000, 10000, 20000 5bills.

V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject Ch\$ 1000	ON											
★ Accept Ch\$ 1000	OFF											
★ Reject Ch\$ 2000		ON										
★ Accept Ch\$ 2000		OFF										
★ Reject Ch\$ 5000			ON									
★ Accept Ch\$ 5000			OFF									
★ Reject Ch\$ 10000				ON								
★ Accept Ch\$ 10000				OFF								
★ Reject Ch\$ 20000					ON							
★ Accept Ch\$ 20000					OFF							
★ Reserved						ON						
★ Reserved						OFF						
★ Harness Disable							ON					
★ Harness Enable							OFF					
★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / Ch\$ 1000								OFF	OFF			
2 pulse / Ch\$ 1000								ON	OFF			
4 pulse / Ch\$ 1000								OFF	ON			
20 pulse / Ch\$ 1000								ON	ON			
★ Pulse Speed	50ms LO / 50ms HI								OFF		OFF	
	60ms LO / 300ms HI								ON		OFF	
	30ms LO / 50ms HI								OFF		ON	
	150ms LO / 150ms HI								ON		ON	

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

V7-CLP5(Pulse/ICT002)

V7 Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
RS232 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

V7 Interface Settings: 3(ICT002)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Mode		ON		
★ ICT002 Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	ICT002
BV1	Ch\$ 1000	Ch\$ 1000
BV2	Ch\$ 2000	Ch\$ 2000
BV3	Ch\$ 5000	Ch\$ 5000
BV4	Ch\$ 10000	Ch\$ 10000
BV5	Ch\$ 20000	Ch\$ 20000