V77E-GBP4
V77E Option Switch Settings : 1(Pulse/ICT104U/MDB)

Supported bill

English banknotes: Bank of England   £ 5, £ 10, £ 20, £ 50
Scottish banknotes: Bank of Scotland   £ 5, £ 10, £ 20
     Royal Bank & & Clydesdale Bank   £ 5, £ 10

V77E dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject £ 5	ON											
Accept £ 5	OFF											
Reject £ 10		ON										
Accept £ 10		OFF										
Reject £ 20			ON									
Accept £ 20			OFF									
Reject £ 50				ON								
Accept £ 50				OFF								
Reserved					ON							
Reserved					OFF							
Reserved						ON						
Reserved						OFF						
Harness Disable							ON					
Harness Enable							OFF					
Inhibit Active High								ON				
Inhibit Active Low								OFF				
1 pulse / £ 5									OFF	OFF		
5 pulses / £ 5									ON	OFF		
10 pulses / £ 5									OFF	ON		
20 pulses / £ 5									ON	ON		
Pulse Speed — 50ms LO / 50ms HI											OFF	OFF
Pulse Speed — 60ms LO / 300ms HI											ON	OFF
Pulse Speed — 30ms LO / 50ms HI											OFF	ON
Pulse Speed — 150ms LO / 150ms HI											ON	ON

★ Manufacture setting

◈ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.
     (2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.
     (3) Use both 2nd and 3rd dip of the internal dip-sitch to change different interface protocol.

V77E-GBP4 (Pulse/ICT104U/MDB)

Interface Settings: 3(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Interface		ON	OFF	
ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
Reserved		OFF	OFF	
Reserved				ON
Reserved				OFF

★ Manufacture setting

Currency Assign Data

Interface / Bill value	ICT104U	Pulse	MDB
BV1	£ 5	£ 5	£ 5
BV2	£ 10	£ 10	£ 10
BV3	£ 20	£ 20	£ 20
BV4	£ 50	£ 50	£ 50

Interface Settings: 3(ICT104U)

INTERFACE	SW1	SW2	SW3	SW4
Reserved	ON			
Reserved	OFF			
Pulse Interface		ON	OFF	
ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
Reserved		OFF	OFF	
Reserved				ON
Reserved				OFF

★ Manufacture setting

Interface Settings: 3(MDB)

INTERFACE	SW1	SW2	SW3	SW4
Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Interface		ON	OFF	
ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
Reserved		OFF	OFF	
Reserved				ON
Reserved				OFF

★ Manufacture setting