V77E-KES3

V77E Option Switch Settings : 1(Pulse/ICT104U/MDB)

Supported bill KES 50, 100, 200   3bills.

V77E dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject KES 50	ON											
★ Accept KES 50	OFF											
Reject KES 100		ON										
★ Accept KES 100		OFF										
Reject KES 200			ON									
★ Accept KES 200			OFF									
Reserved				ON								
★ Reserved				OFF								
Reserved					ON							
★ Reserved					OFF							
Reserved						ON						
★ Reserved						OFF						
Harness Disable							ON					
★ Harness Enable							OFF					
Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / KES 50									OFF	OFF		
2 pulses / KES 50									ON	OFF		
5 pulses / KES 50									OFF	ON		
10 pulses / KES 50									ON	ON		
★ Pulse Speed — 50ms LO / 50ms HI											OFF	OFF
Pulse Speed — 60ms LO / 300ms HI											ON	OFF
Pulse Speed — 30ms LO / 50ms HI											OFF	ON
Pulse Speed — 150ms LO / 150ms HI											ON	ON

★ Manufacture setting

◈ Factory configuration has all switches in the OFF position.

Note : 1.Reset the bill acceptor after setting the dip switch

2.SW6,SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

3.Use both 2nd and 3rd dip of the internal dip-sitch to change different interface protocol.

Appendix

V77E-KES3 (Pulse/ICT104U/MDB)

Interface Settings: 3(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON	OFF	
ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
Reserved		OFF	OFF	
★ Reserved				ON
Reserved				OFF

★ Manufacture setting

Currency Assign Data

Interface / Bill value	ICT104U	Pulse	MDB
BV1	KES 50	KES 50	KES 50
BV2	KES 100	KES 100	KES 100
BV3	KES 200	KES 200	KES 200

Interface Settings: 3(ICT104U)

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
Reserved	OFF			
Pulse Mode		ON	OFF	
★ ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
Reserved		OFF	OFF	
Reserved				ON
★ Reserved				OFF

★ Manufacture setting

Interface Settings: 3(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Interface		ON	OFF	
ICT Interface		OFF	ON	
★ MDB Interface		ON	ON	
Reserved		OFF	OFF	
Reserved				ON
★ Reserved				OFF

★ Manufacture setting