

V77E-RON5

V77E Option Switch Settings : 1(Pulse/ICT104U/MDB)

Supported bill Lei 1, 5, 10, 20, 50 5 bills.

V77E dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject Lei 1	ON											
★ Accept Lei 1	OFF											
★ Reject Lei 5		ON										
★ Accept Lei 5		OFF										
★ Reject Lei 10			ON									
★ Accept Lei 10			OFF									
★ Reject Lei 50				ON								
★ Accept Lei 50				OFF								
★ Reject Lei 20					ON							
★ Accept Lei 20					OFF							
★ Reserved						ON						
★ Reserved						OFF						
Pulse Mode	Other Mode											
★ Harness Disable	BA stops working when fishing						ON					
★ Harness Enable	Normal						OFF					
★ Inhibit Active High							ON					
★ Inhibit Active Low							OFF					
★ 1 pulse / Lei 1								OFF	OFF			
★ 2 pulse / Lei 1								ON	OFF			
★ 5 pulse / Lei 1								OFF	ON			
★ 20 pulse / Lei 1								ON	ON			
★ Pulse Speed	50ms on / 50ms off									OFF	OFF	
	60ms on / 300ms off									ON	OFF	
	30ms on / 50ms off									OFF	ON	
	150ms on / 150ms off									ON	ON	

★ Manufacture setting

Note : (1) Default setting.

(2) Use 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

(3) Remove the front cover and the dip-switch in on the CPU board.

V77E-RON5 (Pulse/ICT104U/MDB)

Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Interface		ON	OFF	
ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
Reserved		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

Interface Settings: 2(ICT104U) Currency Assign Data

INTERFACE	SW1	SW2	SW3	SW4
★ Reserved	ON			
	OFF			
Pulse Interface		ON	OFF	
★ ICT104U Interface		OFF	ON	
MDB Interface		ON	ON	
Reserved		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting

Interface Bill value	Pulse	ICT104U	MDB
BV1	1	1	1
BV2	5	5	5
BV3	10	10	10
BV4	50	50	50
BV5	20	20	20

Interface Settings: 2(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	OFF			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0				
Pulse Interface		ON	OFF	
ICT104U Interface		OFF	ON	
★ MDB Interface		ON	ON	
Reserved		OFF	OFF	
★ Reserved				ON
				OFF

★ Manufacture setting