

V7E/LX7-ANG8(ANG2+AWG2+USD4)

V7E/LX7 Option Switch Settings: 1(MDB)

Supported bill **ANG** 10, 25, 2bills.
 AWG 10, 25, 2bills.
 USD 1, 5, 10, 20 4bills.

V7E dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
	Reject ANG 10 & AWG 10	ON											
★	Accept ANG 10 & AWG 10	OFF											
	Reject ANG 25 & AWG 25		ON										
★	Accept ANG 25 & AWG 25		OFF										
	Reject USD 1 & 5			ON									
★	Accept USD 1 & 5			OFF									
	Reject USD 10				ON								
★	Accept USD 10				OFF								
	Reject USD 20				ON								
★	Accept USD 20				OFF								
	Exchange rate 1 USD=1.75 AWG/ANG					ON							
★	Exchange rate 1 USD=1.00 AWG/ANG					OFF							
	Reserved							ON					
★	Reserved							OFF					
	Reserved							ON					
★	Reserved							OFF					
★	Reserved								OFF	OFF			
	Reserved								ON	OFF			
	Reserved								OFF	ON			
	Reserved								ON	ON			
★	Reserved										OFF	OFF	
	Reserved										ON	OFF	
	Reserved										OFF	ON	
	Reserved										ON	ON	

★ Manufacture setting

Note : Reset the bill acceptor after setting the dip switch.

V7E/LX7-ANG8(MDB)

DIP SWITCHES SETTING : 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
		OFF			
	Reserved		ON		
★	Reserved		OFF		
	Reserved			ON	
★	Reserved			OFF	
★	Reserved				ON
★	Reserved				OFF

★ Manufacture setting

Note : Remove the front cover and the dip-switch in on the CPU board.

Currency Assign Data

Interface Bill value	MDB
BV1	ANG 10 & AWG 10
BV2	ANG 25 & AWG 25
BV3	USD 1
BV4	USD 5
BV5	USD 10
BV6	USD 20