

V7E/LX7-BYN4

V7E/LX7 Option Switch Settings: 1(Pulse/ICT104U/RS232 A0/ccNet)

Supported bill BYN 5, 10, 20, 50 4 bills.

V7E/LX7 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject BYN 5	ON											
	Accept BYN 5	OFF											
	Reject BYN 10		ON										
★	Accept BYN 10		OFF										
	Reject BYN 20			ON									
★	Accept BYN 20			OFF									
	Reject BYN 50				ON								
★	Accept BYN 50				OFF								
	Reserved				ON								
★	Reserved				OFF								
	Reserved					ON							
★	Reserved					OFF							
	Harness Disable						ON						
★	Harness Enable						OFF						
	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulse / BYN 5								OFF	OFF			
	5 pulses / BYN 5								ON	OFF			
	10 pulses / BYN 5								OFF	ON			
	50 pulses / BYN 5								ON	ON			
★	Pulse Speed	50ms LO / 50ms HI								OFF	OFF		
		60ms LO / 300ms HI								ON	OFF		
		30ms LO / 50ms HI								OFF	ON		
		150ms LO / 150ms HI								ON	ON		

★ Manufacture setting

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

(3) Use 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

V7E/LX7-BYN4(Pulse/ICT104U/RS232 A0/ccNet)

DIP SWITCHES SETTING: 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

DIP SWITCHES SETTING: 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

DIP SWITCHES SETTING: 2(ccNet)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
	9600 Baud rate	OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	RS232 A0	ccNet	ICT104U
BV1	BYN 5	BYN 5	BYN 5	BYN 5
BV2	BYN 10	BYN 10	BYN 10	BYN 10
BV3	BYN 20	BYN 20	BYN 20	BYN 20
BV4	BYN 50	BYN 50	BYN 50	BYN 50

DIP SWITCHES SETTING: 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Mode		OFF	OFF	
	ccNet Mode		ON	ON	
★	RS232 A0 Mode		OFF	ON	
★	Reserved				ON
					OFF

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	BYN 5
2	BYN 10
3	BYN 20
4	BYN 50

★ Manufacture setting