

GP58

Thermal Printer

- Full / partial cut function
- User-friendly multiple interfaces
- Easy installation and low maintenance
- Fast printing speed
- Anti-jam / anti-drag technology **GP58 III**
- 12V / 24V power consumption available **GP58 III**
- Larger capacity Micro SD card included for volume data storage **GP58 III**
- Support small & large paper rolls **GP58 III**
- ESC/POS command support **GP58 III**



ict

GP58

Thermal Printer

The GP-58 Series has a built-in real time clock for the ticket time stamping. Its excellent reporting system provides daily and summary transaction reports. The GP-58 Series stores up to 365 days of daily reports, and the reports can be deleted if no longer needed.

Both coupon and receipt are customizable. The downloadable design provides the flexibility to use the customized ticket formats and logos in an easy way. Using the GP-58 Series software tools, the designed format can be saved for later use.

Specifications



Printing Method

Thermal dot-line printing



Printing Speed

GP58 CA/CR: Up to 40mm/sec

GP58 III: Up to 90 mm/sec (96 dots)



Paper Size

GP58 CA/CR:

Width: 56±0.5mm/ 2.2±0.02 inches

Outside Diameter: 65±0.5mm/ 2.56±0.02 inches

GP58 III:

Width: 56±0.5mm/ 2.2±0.02 inches

<Small Paper Roll>:

Outside Diameter: 65±0.5mm/ 2.56±0.02 inches

<Large Paper Roll>:

Outside Diameter: 130±0.5mm/ 5.12±0.02 inches



Resolution

8 dots/ mm



Character Set

3 Fonts (8*13, 16*24, 24*36)



Interface

Pulse, Hopper, Pot of Gold, FOD, ESC/POS
Setting /download: RS232, USB



Power Source

GP58 CA/CR: 12V

GP58 III: 12V/24V



Recommended Applications

Indoor Gaming, Vending, Kiosk, Amusement



Power Consumption

GP58 CA/CR: (12V)

Standby: 0.16A, 2W

Operation: 2.5A, 30W

Maximum: 3.75A, 45W

GP58 III: (12V & 24V)

Standby: 12V/0.14A, 1.68W, 24V/ 0.1A, 2.4W

Operation: 12V/1.2A, 14.4W, 24V/0.6A, 14.4W

Maximum: 12V/6A, 72W, 24V/3.5A, 84W



Dimension

GP58 CA/CR:

154 x 91.4 x 102mm/

6.06 x 3.6 x 4.02 inches(with Paper Roll)

147 x 91.4 x 102mm/ 5.79 x 3.6 x 4.02 inches

GP58 III:

<Small Paper Roll>:

153.1 x 91.65 x 104.9mm/

6.03 x 3.61 x 4.13 inches(with Paper Roll)

152.5 x 90.85 x 98mm/ 6 x 3.58 x 3.85 inches

<Large Paper Roll>:

157.5 x 91.65 x 215.1mm/

6.2 x 3.61 x 8.47 inches(with Paper Roll)

152.5 x 90.85 x 164.7mm/ 6 x 3.57 x 6.48 inches



Weight

GP58 CA/CR: Approx. 700g /1.55 lbs

GP58 III: Small Paper Roll Approx. 750 g /1.66 lbs

Large Paper Roll Approx. 850 g /1.88 lbs



Environmental

GP58 CA/CR:

Operation Temperature: 0°C/32°F~50°C/122°F

Storage Temperature: -20°C/-4°F~60°C/140°F

Humidity: 30%~85% (no condensation)

GP58 III:

Operation Temperature: 0°C/32°F~50°C/122°F

Storage Temperature: -30°C/-22°F~60°C/140°F

Humidity: 10%~85% (no condensation)



GP58 III



Large paper roll

GP58 III



Specifications are subject to change without prior notice.
All trademarks and copyrights mentioned herein belong to their respective owners.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email : sales@ictgroup.com.tw (Product Information)

rma@ictgroup.com.tw (Technical Service)

Website : www.ictgroup.com.tw