

## BAM4

### L77&L77F-P3/P6 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill BAM 10, 20, 50, 100 4bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / BAM 10	OFF	OFF	OFF							
	2 Pulse / BAM 10	OFF	OFF	ON							
	3 Pulse / BAM 10	OFF	ON	OFF							
	4 Pulse / BAM 10	OFF	ON	ON							
	5 Pulse / BAM 10	ON	OFF	OFF							
	10 Pulse / BAM 10	ON	OFF	ON							
	20 Pulse / BAM 10	ON	ON	OFF							
	100 Pulse / BAM 10	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept BAM 10						ON				
	Reject BAM 10						OFF				
★	Accept BAM 20							ON			
	Reject BAM 20							OFF			
★	Accept BAM 50								ON		
	Reject BAM 50								OFF		
★	Accept BAM 100									ON	
	Reject BAM 100									OFF	
	Reserved										ON
★	Reserved										OFF

★ Manufacture setting

Note:(1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

## L77&L77F-BAM4(Pulse/RS232 A0)

### DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	RS232 A0 Protocol Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
					OFF

★ Manufacture setting

### DIP SWITCHES SETTING : 3(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON		
★	RS232 A0 Protocol Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
					OFF

★ Manufacture setting

ESCROW DATA	
Code	Denomination
61h	Reserved
62h	Reserved
63h	Reserved
64h	BAM 10
65h	BAM 20
66h	BAM 50
67h	BAM 100
68h	Reserved
69h	Reserved

CURRENCY ASSIGN DATA			
Code	Country	Denomination	EXP
61h	00h	00h	00h
62h	00h	00h	00h
63h	00h	00h	00h
64h	75h	0Ah	00h
65h	75h	14h	00h
66h	75h	32h	00h
67h	75h	64h	00h
68h	00h	00h	00h
69h	00h	00h	00h

### Currency Assign Data

Interface Bill value	Pulse	RS232 A0
BV1	BAM 10	BAM 10
BV2	BAM 20	BAM 20
BV3	BAM 50	BAM 50
BV4	BAM 100	BAM 100