

# JPY4

## L77&L77F DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill ￥ 1000, 2000, 5000, 10000 4bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / ￥ 1000	OFF	OFF	OFF							
	2 Pulse / ￥ 1000	OFF	OFF	ON							
	3 Pulse / ￥ 1000	OFF	ON	OFF							
	4 Pulse / ￥ 1000	OFF	ON	ON							
	5 Pulse / ￥ 1000	ON	OFF	OFF							
	10 Pulse / ￥ 1000	ON	OFF	ON							
	20 Pulse / ￥ 1000	ON	ON	OFF							
	100 Pulse / ￥ 1000	ON	ON	ON							
★	Fast output Pulse Lo= 50ms Hi=100ms				ON						
	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept ￥ 1000						ON				
	Reject ￥ 1000						OFF				
★	Accept ￥ 2000							ON			
	Reject ￥ 2000							OFF			
★	Accept ￥ 5000								ON		
	Reject ￥ 5000								OFF		
★	Accept ￥ 10000									ON	
	Reject ￥ 10000									OFF	
	Reserved										ON
★	Reserved										OFF

## DIP SWITCHES SETTING : 2

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	ICT Protocol Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
★					OFF

### Currency Assign Data

Interface Bill value	Pulse	ICT
BV1	￥ 1000	￥ 1000
BV2	￥ 2000	￥ 2000
BV3	￥ 5000	￥ 5000
BV4	￥ 10000	￥ 10000

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

## Appendix