

L77&L77F-XOF4

L77&L77F DIP SWITCHES SETTING : 1(Pulse/Out of service/ICT104U)

Supported bill Fr 500, 1000, 2000, 5000 4bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / Fr 500	OFF	OFF	OFF							
	2 Pulse / Fr 500	OFF	OFF	ON							
	3 Pulse / Fr 500	OFF	ON	OFF							
	4 Pulse / Fr 500	OFF	ON	ON							
	5 Pulse / Fr 500	ON	OFF	OFF							
	10 Pulse / Fr 500	ON	OFF	ON							
	20 Pulse / Fr 500	ON	ON	OFF							
	100 Pulse / Fr 500	ON	ON	ON							
★	Fast output Pulse Lo= 50ms Hi=100ms				ON						
	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept Fr 500						ON				
	Reject Fr 500						OFF				
★	Accept Fr 1000							ON			
	Reject Fr 1000							OFF			
★	Accept Fr 2000								ON		
	Reject Fr 2000								OFF		
★	Accept Fr 5000									ON	
	Reject Fr 5000									OFF	
	Reserved										ON
★	Reserved										OFF

DIP SWITCHES SETTING : 2 Currency Assign Data

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	ICT104U Protocol Mode		OFF		
	Reserved			ON	
★	Reserved			OFF	
	Reserved				ON
★	Reserved				OFF

Interface Bill value	Pulse	ICT104U
BV1	Fr 500	Fr 500
BV2	Fr 1000	Fr 1000
BV3	Fr 2000	Fr 2000
BV4	Fr 5000	Fr 5000

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

(3)Out of service:Normal High,Error Low.

Appendix