

L77F/PL77-GBP2

L77F/PL77 DIP SWITCHES SETTING : 1(Pulse/Out of service/ICT104U/MDb)

Supported bill

【England】 Bank of England : 5 、 10 2bills

【Scotland】 Bbank of Scotland : 5 、 10 2bills

Clydesdale Bank : 5 、 10 2bills

Royal Bank of Scotland : 5 、 10 2bills

【Northern Ireland】 Bank of Ireland : 5 、 10 2bills

Ulster Bank : 5 、 10 2bills

Danske Bank : 10 1bills

First Trust Bank : 10 1bills

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / £ 5	OFF	OFF	OFF							
	2 Pulse / £ 5	OFF	OFF	ON							
	3 Pulse / £ 5	OFF	ON	OFF							
	4 Pulse / £ 5	OFF	ON	ON							
	5 Pulse / £ 5	ON	OFF	OFF							
	10 Pulse / £ 5	ON	OFF	ON							
	20 Pulse / £ 5	ON	ON	OFF							
	100 Pulse / £ 5	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept £ 5						ON				
	Reject £ 5						OFF				
★	Accept £ 10							ON			
	Reject £ 10							OFF			
★	Reserved								ON		
	Reserved								OFF		
★	Reserved									ON	
	Reserved									OFF	
★	Reserved										ON
	Reserved										OFF

Currency Assign Data

Interface Bill value	Pulse	MDb	ICT104U
BV1	£ 5	£ 5	£ 5
BV2	£ 10	£ 10	£ 10

Appendix

L77F/PL77-GBP2 (Pulse/Out of service/ICT104U/MDb)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON	OFF	
	ICT104U Protocol Mode		OFF	ON	
	MDb Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

DIP SWITCHES SETTING : 2(ICT104U)

	FUNCTION	SW1	SW2	SW3	SW4
	Not used	ON			
	Not used	OFF			
	Pulse Mode		ON	OFF	
★	ICT104U Protocol Mode		OFF	ON	
	MDb Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

DIP SWITCHES SETTING : 2(MDb)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON	OFF	
	ICT104U Protocol Mode		OFF	ON	
★	MDb Mode		ON	ON	
	Reserved		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Note:(1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

(3)Out of service:Normal Low,Error High.