

L77F/PL77-UYU7

L77F/PL77 DIP SWITCHES SETTING : 1(Pulse/RS232 A0)

Supported bill UYU 20, 50, 100, 200, 500, 1000, 2000 7bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / UYU 10	OFF	OFF	OFF							
	2 Pulses / UYU 10	OFF	OFF	ON							
	3 Pulses / UYU 10	OFF	ON	OFF							
	4 Pulses / UYU 10	OFF	ON	ON							
	5 Pulses / UYU 10	ON	OFF	OFF							
	10 Pulses / UYU 10	ON	OFF	ON							
	20 Pulses / UYU 10	ON	ON	OFF							
	100 Pulses / UYU 10	ON	ON	ON							
	Fast output Pulse Lo= 50ms Hi=100ms				ON						
★	Slow output Pulse Lo= 50ms Hi=300ms				OFF						
	Inhibit level Active Low				ON						
★	Inhibit level Active High				OFF						
★	Accept UYU 20				ON						
	Reject UYU 20				OFF						
★	Accept UYU 50				ON						
	Reject UYU 50				OFF						
★	Accept UYU 100				ON						
	Reject UYU 100				OFF						
★	Accept UYU 200 & 500				ON						
	Reject UYU 200 & 500				OFF						
★	Accept UYU 1000 & 2000				ON						
	Reject UYU 1000 & 2000				OFF						

★ Manufacture setting

Note:(1) Please reset the bill acceptor after set the dip switch.

(2) Dip switches 1 to 5 are only used for pulse protocol.

L77F/PL77-UYU7(Pulse/RS232 A0)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	RS232 A0 Interface Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
					OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON		
★	RS232 A0 Interface Mode		OFF		
★	Reserved			ON	
				OFF	
					ON
					OFF

★ Manufacture setting

RS232 A0 INFORMATION	
BillType Data	
Code	Denomination
1	Reserved
2	UYU 20
3	UYU 50
4	UYU 100
5	UYU 200
6	UYU 500
7	UYU 1000
8	UYU 2000

Currency Assign Data

Interface Bill value	Pulse	RS232 A0
BV1	UYU 20	UYU 20
BV2	UYU 50	UYU 50
BV3	UYU 100	UYU 100
BV4	UYU 200	UYU 200
BV5	UYU 500	UYU 500
BV6	UYU 1000	UYU 1000
BV7	UYU 2000	UYU 2000