

S7ER

V7E SERIES



S7ER

FEATURES

- Four-way bill insertion.
- Auto-calibrating.
- Secure double-lock removable bill box capacity: 65 bills and 200 bills available.
- RFID function bill box available (function with Docking Station).

SPECIFICATIONS

Acceptance Rate

96% or greater.

*Note: The incomplete bills such as extremely dirty, wet, broken or wrinkle ones are excluded.

Interface

Pulse, ICT Protocol (RS232)

Bill Box Capacity

P60: Approx. 65 bills

P2 : Approx. 200 bills

Bill Accepted Width

62~72 mm

Transaction Speed

Approx. 3 seconds to stack

Bill Insertion

Four way acceptable

Power Source

12V DC (10~16V DC)

Power Consumption

Normal Mode-

Standby : 0.38A, 4.56W

Operation: 2 A, 24 W

Maximum: 2.5 A, 30 W

Power Saving Mode-

Mode1 : 70uA, 0.84mW

Mode2 : 15uA, 0.18mW

Weight

Approx. 1.5 kg

Operation Environment

Operation Temperature: -5 °C~60 °C

Storage Temperature: -30 °C~70 °C

Humidity: 30%~95% RH
(no condensation)

Installation

Indoor/ Outdoor

Application

Vending, Kiosk