

PLN4

P70/P2/P5 DIP SWITCHES SETTING : 1(Pulse/M.D.B)

Supported bill PLN 10, 20, 50, 100 4bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10		
★	1 Pulse / PLN 10	OFF	OFF	OFF									
	2 Pulse / PLN 10	OFF	OFF	ON									
	3 Pulse / PLN 10	OFF	ON	OFF									
	4 Pulse / PLN 10	OFF	ON	ON									
	5 Pulse / PLN 10	ON	OFF	OFF									
	10 Pulse / PLN 10	ON	OFF	ON									
	20 Pulse / PLN 10	ON	ON	OFF									
	100 Pulse / PLN 10	ON	ON	ON									
★	Fast output Pulse Lo= 50ms Hi=100ms				ON								
	Slow output Pulse Lo= 50ms Hi=300ms				OFF								
★	Inhibit level Active Low				ON								
	Inhibit level Active High				OFF								
★	Accept PLN 10					ON							
	Reject PLN 10					OFF							
★	Accept PLN 20							ON					
	Reject PLN 20							OFF					
★	Accept PLN 50								ON				
	Reject PLN 50								OFF				
★	Accept PLN 100									ON			
	Reject PLN 100									OFF			
★	Reserved										ON		
	Reserved										OFF		

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

P70-PLN4/P2/P5(Pulse/M.D.B)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
★	Pulse Mode		ON		
	M.D.B Interface		OFF		
	Harness Disable			ON	
★	Harness Enable			OFF	
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting

DIP SWITCHES SETTING : 2(M.D.B)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Mode		ON		
★	M.D.B Interface		OFF		
	Reserved			ON	
★	Reserved			OFF	
	Manufacture Default				ON
★	System Default				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	PLN 10	PLN 10
BV2	PLN 20	PLN 20
BV3	PLN 50	PLN 50
BV4	PLN 100	PLN 100