

TAO-A.V-IDR5

TAO-A.V Option Switch Settings: 1(Pulse/ICT104U)

Supported bill Rp 5000, 10000, 20000, 50000, 100000 5bills.

TAO-A.V dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject Rp 5000 & 10000	ON											
★	Accept Rp 5000 & 10000	OFF											
★	Reject Rp 20000		ON										
★	Accept Rp 20000		OFF										
★	Reject Rp 50000			ON									
★	Accept Rp 50000			OFF									
★	Reject Rp 100000				ON								
★	Accept Rp 100000				OFF								
★	High Security					ON							
★	High Acceptance (Note.2)					OFF							
★	Reserved						ON						
★	Reserved						OFF						
	Pulse Mode	Other Mode											
★	Harness Disable	BA stops working when fishing						ON					
★	Harness Enable	Normal						OFF					
★	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulses / Rp 1K								OFF	OFF			
★	5 pulses / Rp 1K								ON	OFF			
★	10 pulses / Rp 1K								OFF	ON			
★	20 pulses / Rp 1K								ON	ON			
★	Interface Timing Conversion	50ms LO / 50ms HI									OFF	OFF	
		60ms LO / 300ms HI									ON	OFF	
		30ms LO / 50ms HI									OFF	ON	
		150ms LO / 150ms HI									ON	ON	

★ Manufacture setting

Note : (1) Default setting

(2) High acceptance mode will increasing accepting rate, however, it will reduce the security level of Bill Acceptor.

Appendix

TAO-A.V-IDR5(Pulse/ICT104U)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
★	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
★	ICT104U Interface		OFF		
★	Reserved			ON	
★	Reserved			OFF	
★	Reserved				ON
★	Reserved				OFF

★ Manufacture setting

Interface Settings: 2(ICT104U)

	INTERFACE	SW1	SW2	SW3	SW4
★	Not Used	ON			
★	Not Used	OFF			
★	Pulse Mode		ON		
★	ICT104U Interface		OFF		
★	Reserved			ON	
★	Reserved			OFF	
★	Reserved				ON
★	Reserved				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	ICT104U	Pulse
BV1		
BV2		
BV3	5000	5000
BV4	10000	10000
BV5	20000	20000
BV6	50000	50000
BV7	100000	100000