

TAO-A.V-MUP4(MXP2+USD2)

TAO-A.V Option Switch Settings: 1(Pulse/ICT104V/ICT002U/MDB)

Supported bill N\$ 20, 50 2bills.
USD 1, 5 2bills.

TAO-V dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject USD 1	ON											
★	Accept USD 1	OFF											
★	Reject N\$ 20		ON										
★	Accept N\$ 20		OFF										
★	Reject N\$ 50			ON									
★	Accept N\$ 50			OFF									
★	Reject USD 5				ON								
★	Accept USD 5				OFF								
★	Reserved				ON								
★	Reserved				OFF								
★	Reserved				ON								
★	Reserved				OFF								
★	Harness Disable					ON							
★	Harness Enable					OFF							
★	Inhibit Active High						ON						
★	Inhibit Active Low						OFF						
★	1 pulse / N\$ 10 / USD \$1							OFF	OFF				
★	2 pulses / N\$ 10 / USD \$1							ON	OFF				
★	5 pulses / N\$ 10 / USD \$1							OFF	ON				
★	10 pulses / N\$ 10 / USD \$1							ON	ON				
★	Interface Timing Conversion	50ms HI / 50ms LO								OFF	OFF		
		300ms HI / 60ms LO								ON	OFF		
		50ms HI / 30ms LO								OFF	ON		
		150ms HI / 150ms LO								ON	ON		

★ Default setting

Use 2nd dip switch of the internal dip-switch to change different interface protocol.

◆ Note : (1) For Accepting US Dollars, make sure you have dip 5 set to ON position.

(Exchange Rate on USD to MXP is 1:15 for MDB Mode)

Appendix

TAO-A.V-MUP4(MXP2+USD2)(Pulse/ICT104V/ICT002U/MDB)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON	OFF	
	ICT002U Mode		OFF	ON	
	ICT104V Mode		ON	ON	
	MDB Mode		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	ICT	Pulse	MDB
BV1	USD \$1	USD \$1	USD \$1
BV2	N\$ 20	N\$ 20	N\$ 20
BV3	N\$ 50	N\$ 50	N\$ 50
BV4	USD \$5	USD \$5	USD \$5

Interface Settings: 2(ICT002U/ICT104V)

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
★	ICT002U Mode		OFF	ON	
	ICT104V Mode		ON	ON	
	MDB Mode		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting

★ Manufacture setting

TAO-V-MUP4(MXP2+USD2)

Interface Settings: 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	OFF			
	Pulse Mode		ON	OFF	
	ICT002U Mode		OFF	ON	
	ICT104V Mode		ON	ON	
★	MDB Mode		OFF	OFF	
★	Reserved				ON
					OFF

★ Manufacture setting