

TAO-V Option Switch Settings: 1(Pulse/MDB)

Supported bill Rp 1000, 2000, 5000, 10000, 20000 5bills.

TAO-V dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject Rp 1000	ON											
★	Accept Rp 1000	OFF											
★	Reject Rp 2000		ON										
★	Accept Rp 2000		OFF										
★	Reject Rp 5000			ON									
★	Accept Rp 5000			OFF									
★	Reject Rp 10000				ON								
★	Accept Rp 10000				OFF								
★	Reject Rp 20000					ON							
★	Accept Rp 20000					OFF							
★	Reserved					ON							
★	Reserved					OFF							
★	Harness Disable						ON						
★	Harness Enable						OFF						
★	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulse / Rp 1000								OFF	OFF			
★	5 pulse / Rp 1000								ON	OFF			
★	10 pulse / Rp 1000								OFF	ON			
★	20 pulse / Rp 1000								ON	ON			
★	Interface Timing Conversion	50ms on / 50ms off								OFF	OFF		
		60ms on / 300ms off								ON	OFF		
		30ms on / 50ms off								OFF	ON		
		150ms on / 150ms off								ON	ON		

★ Manufacture setting

◆ Note : (1) Please reset the bill acceptor after any changes on Dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
★	Reserved			ON	
★				OFF	
★					ON
★					OFF

★ Manufacture setting

Interface Settings: 3(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
★	Pulse Mode		ON		
★	MDB Interface		OFF		
★	Reserved			ON	
★				OFF	
★					ON
★					OFF

★ Manufacture setting