

TAO-V-MUP4(MXP2+USD2)

TAO-V Option Switch Settings: 1(Pulse/MDB)

**Supported bill MXP 20, 50
USD 1, 5 4bills.**

TAO-V dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject USD 1	ON											
	Accept USD 1	OFF											
★	Reject MXP 20		ON										
★	Accept MXP 20		OFF										
★	Reject MXP 50			ON									
★	Accept MXP 50			OFF									
★	Reject USD 5				ON								
★	Accept USD 5				OFF								
★	Reserved				ON								
★	Reserved				OFF								
★	Reserved				ON								
★	Reserved				OFF								
	Pulse Mode	Other Mode											
★	Harness Disable	BA stops working when fishing				ON							
★	Harness Enable	Normal				OFF							
★	Inhibit Active High					ON							
★	Inhibit Active Low					OFF							
★	1 pulse / MXP 10 & USD 1								OFF	OFF			
	2 pulses / MXP 10 & USD 1								ON	OFF			
	5 pulses / MXP 10 & USD 1								OFF	ON			
	10 pulses / MXP 10 & USD 1								ON	ON			
★	Interface Timing Conversion	50ms LO / 50ms HI									OFF	OFF	
		60ms LO / 300ms HI									ON	OFF	
		30ms LO / 50ms HI									OFF	ON	
		150ms LO / 150ms HI									ON	ON	

★ Default setting

★★ Use 2nd dip switch of the internal dip-switch to change different interface protocol.

Note :1. For Accepting US Dollars Exchange Rate on USD to MXP is 1:18 for MDB Mode

TAO-V-MUP4(MXP2+USD2)(Pulse/MDB)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
★	Reserved			ON	
★				OFF	
★					ON
★					OFF

★ Manufacture setting

Interface Settings: 2(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	OFF			
★	Pulse Mode		ON		
★	MDB Interface		OFF		
★	Reserved			ON	
★				OFF	
★					ON
★					OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	USD 1	USD 1
BV2	MXP 20	MXP 20
BV3	MXP 50	MXP 50
BV4	USD 5	USD 5