

TAO-V-MXN5

TAO-V Option Switch Settings: 1(Pulse/MDB)

Supported bill MXN 20, 50, 100, 200, 500 5bills.

TAO-V dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject MXN 20	ON											
	Accept MXN 20	OFF											
★	Reject MXN 50		ON										
★	Accept MXN 50		OFF										
	Reject MXN 100			ON									
★	Accept MXN 100			OFF									
	Reject MXN 200				ON								
★	Accept MXN 200				OFF								
	Reject MXN 500					ON							
★	Accept MXN 500					OFF							
	Reserved					ON							
★	Reserved					OFF							
	Pulse Mode	Other Mode											
	Harness Disable	BA stops working when fishing						ON					
★	Harness Enable	Normal						OFF					
	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulse / MXN 10								OFF	OFF			
	2 pulses / MXN 10								ON	OFF			
	5 pulses / MXN 10								OFF	ON			
	10 pulses / MXN 10								ON	ON			
★	Interface Timing Conversion	50ms LO / 50ms HI									OFF	OFF	
		60ms LO / 300ms HI									ON	OFF	
		30ms LO / 50ms HI									OFF	ON	
		150ms LO / 150ms HI									ON	ON	

★ Manufacture setting

Note : (1) Default setting

(2) Use 2nd dip switch of the internal dip-switch to change different interface protocol.

TAO-V-MXN5(Pulse/MDB)

Interface Settings: 2(Pulse) Currency Assign Data

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	MDB Interface		OFF		
★	Reserved			ON	
	Reserved			OFF	
★	Reserved				ON
	Reserved				OFF

★ Manufacture setting

Interface Bill value	Pulse	MDB
BV1	MXN 20	MXN 20
BV2	MXN 50	MXN 50
BV3	MXN 100	MXN 100
BV4	MXN 200	MXN 200
BV5	MXN 500	MXN 500

Interface Settings: 2(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	OFF			
	Pulse Mode		ON		
★	MDB Interface		OFF		
	Reserved			ON	
★	Reserved			OFF	
	Reserved				ON
★	Reserved				OFF

★ Manufacture setting